

## DECLARATION


---

I, Nurhak AKDOGAN, of PONTET & ALLANO s.a.r.l.,  
6 avenue du Général de Gaulle, 78000 VERSAILLES, France  
do solemnly and sincerely declare :

1. that I am well acquainted with both the English and French languages,  
and
2. that the attached document is a true and correct translation of the specification and drawings accompanying the application for patent made in French Patent Application No. 03 04842 filed on 17<sup>th</sup> April 2003, the priority of which is claimed in U.S. Patent Application No. 10/553,472 filed on 17<sup>th</sup> April 2004,

and I make this declaration conscientiously believing the statement contained herein to be true in every particular.

Dated this 6<sup>th</sup> day of October 2009

  
Nurhak AKDOGAN

"Method and device for the detection and identification of  
objects, secure containers and systems  
which are provided with this device,  
and objects adapted to this method"

5

The present invention relates to a method for the  
detection and identification of objects. It is also aimed  
at a device for the detection and identification of objects  
using this method, objects containers and systems provided  
10 with this device, as well as objects adapted to this method.

There is a requirement for the detection and  
identification of objects which are of a sensitive nature  
in terms of security, such as keys and bunches of keys or  
weapons. Lockable cabinets containing modules provided for  
15 receiving keys are already known, these receiver modules  
being able to be equipped with locking means. Likewise,  
secure cabinets for storing weapons comprising devices for  
locking these weapons already exist.

The objects intended to be stored in these cabinets are  
20 generally provided with identification means such as  
electronic contact identification components of the  
"Dallas" type or components of the RF tag type. The  
locking devices associated with these objects include  
reader modules provided to cooperate with these  
25 identification components.

In the specific case of a lockable cupboard, providing  
identification and locking for each key or bunch of keys  
provided with identification means currently requires the  
provision of as many reader modules as locking modules of  
30 these keys or bunches of keys. As a result, production  
costs are incurred for a large capacity lockable cabinet,  
because of the unit cost of each reader module.

The purpose of the present invention is to propose a  
method for the detection and identification of a plurality  
35 of objects, which allows a significant reduction in the  
cost of producing secure equipment for storing such objects.

This objective is achieved with a method for the  
detection and identification of an object provided with  
identification means and wireless transmission means, this

object being present close to one receiver module among a plurality of receiver modules, this method comprising:

- an electromagnetic coupling between the wireless transmission means of said object and a fixed antenna which is associated with said receiver module, and
- an electrical coupling between said fixed antenna of the receiver module and a secondary fixed antenna which is common to all of said fixed antennae of the receiver module, this common secondary fixed antenna being electromagnetically coupled to a primary fixed antenna which is connected to a reader module which is designed to read the identification data originating from said identification means.

The detection and identification method according to the invention thus allows the production of a system requiring only one reader module designed to communicate with a plurality of objects, which helps to significantly reduce the production costs.

The secondary fixed antenna can be electrically coupled to each of the fixed antennae of each receiver module in succession.

Each electromagnetic coupling between a fixed antenna of a receiver module and wireless transmission means of an object can advantageously induce a supply, by inductive coupling, of electrical energy originating from a power supply module connected to the primary fixed antenna, to the identification means within said object.

Each electromagnetic coupling between a fixed antenna of a receiver module and wireless transmission means of an object can also allow a transmission of identification data transmitted by the identification means of said object towards the reader module.

In an advantageous embodiment of the method according to the invention, this method also comprises a processing of the identification data originating from the identification means of an object, and a selective control of the locking/locking means which are associated with the receiver module whose antenna is electromagnetically coupled to the wireless transmission means of said object.

In a particular version of the invention, the secondary fixed reading antenna is connected to the fixed reception antenna via a plurality of link sections in a cascade each comprising an electrical link between a secondary intermediate antenna of the link section and a primary intermediate antenna of this link section and an electromagnetic coupling between this primary intermediate antenna and a secondary intermediate antenna of a following link section.

According to another aspect of the invention, a device for the detection and identification of an object provided with identification means and wireless transmission means is proposed, this object being present close to one receiver module among a plurality of receiver modules, this device comprising:

- a plurality of fixed antennae each associated with one receiver module of the plurality of receiver modules,
- means for selectively connecting one antenna of said plurality of fixed antennae to a common secondary fixed antenna,
- a primary fixed antenna electromagnetically coupled to the secondary fixed antenna, and
- a common reader module designed to read the identification data originating from said identification means, this reader module being connected to the primary fixed antenna.

The selective connection means are arranged in order to connect each fixed antenna of the module to the secondary fixed antenna in sequence.

The detection and identification device according to the invention can also advantageously comprise a power supply module connected to the primary fixed antenna, this module being arranged in order to transmit electrical energy to the identification means of an object whose wireless transmission means are in an inductive coupling with a fixed antenna of a receiver module, via the electromagnetic coupling between the primary fixed antenna and the secondary antenna and the electromagnetic coupling between the fixed antenna of the receiver module and the wireless transmission means of said object.

According to yet another aspect of the invention, equipment for housing in a secure manner a plurality of objects each provided with identification means and wireless transmission means is proposed, comprising:

5 - a group of modules designed to each receive one object among said plurality of objects, each receiver module comprising means for selectively blocking/locking an object, and

10 - means for controlling said selective blocking/locking means,

characterized in that it also comprises a plurality of fixed antennae each associated with one receiver module among the plurality of receiver modules,

15 - means for selectively connecting one antenna among said plurality of fixed antennae to a common secondary fixed antenna, and

20 - a common reader module designed to read the identification data originating from said identification means, this reader module being connected to the primary fixed antenna and cooperating with the control means.

When the equipment is provided for the management of a set of keys, each receiver module can then comprise:

25 - a housing arranged to receive a mechanical coupling part of a key or a key ring, this part including the wireless transmission means,

30 - a fixed antenna of the module arranged close to said housing so as to realize an electromagnetic coupling between said fixed antenna and the wireless transmission means of an object whose mechanical coupling part is engaged in the receiver housing, and

35 - an electromagnet comprising a mobile part arranged so as to engage in said mechanical coupling part.

The mechanical coupling part can have one end which comprises in an substantially cylindrical cavity the wireless transmission means and the identification means of the object.

40 The mechanical coupling part can for example comprise:

- a first part comprising:

- a head which includes the wireless transmission means and the identification means,

- a shielded part for receiving the mobile part of a blocking/locking electromagnet,

5       - a non-reversible mechanical coupling part, and

- a second part comprising at least one housing for receiving the non-reversible mechanical coupling part of the first part.

10       Equipment according to the invention can also be arranged to store, in a secure manner, weapons provided with identification means and wireless transmission means.

According to yet another aspect of the invention, a system for the detection and identification of a vehicle on  
15 a parking space of a parking area, using the method according to the invention, is proposed, characterized in that this parking space comprises a fixed reception antenna electrically connected to a primary antenna common to all of the parking spaces of this parking area and  
20 electromagnetically coupled to an antenna of a common reader module, this vehicle being equipped with an identifier module comprising an antenna arranged inside the vehicle in order to be electromagnetically coupled to the fixed reception antenna of this parking space when the  
25 vehicle is parked in this parking space.

The identifier module of the vehicle can be included in one and/or more of the number plates of the vehicle, and be provided in the form of a chip or radiofrequency tag (RF tag).

30       Other advantages and characteristics of the invention will become apparent on examination of the detailed description of an embodiment which is in no way limitative, and the attached drawings in which:

- Figure 1 diagrammatically illustrates, as the prior  
35 art, the principle of proximity radio frequency identification used in the detection and identification method according to the invention;

- Figure 2 diagrammatically illustrates the principle of the detection and identification method according  
40 to the invention;

35 If the distance between the antenna A0 and the antenna A2 is sufficiently small as to allow the induction of a sufficient current, then the electronics of the identifier transmits its radio frequency number via the antenna A0. This number is picked up by the antenna A2 then decoded by the electronics of the reader. The distances between

30 in an antenna A0 by an antenna A2. the power supply of the electronics of a reader and induced identifier component are powered by the current produced by 1. According to this principle, the electronics of an radio frequency identification (RFID) illustrated by figure This method uses the well known principle of proximity be described, with reference to the figures mentioned above.

25 identification method according to the invention will now The operating principle of the detection and vehicles in a group of parking spaces.

20 - Figure 8 illustrates an application of the method according to the invention in order to produce a system for the detection and identification of

15 - Figure 7 illustrates a detection and identification system according to the invention, mounted in cascade and - Figure 8 illustrates an application of the method according to the invention in order to produce a system for the detection and identification of

10 - Figure 5C is a simplified perspective view of a receiver module corresponding to the rack of receiver modules represented in figures 5A to 5C; - Figures 6A and 6B are respectively a side view and a top view of a key ring according to the invention; - Figure 7 illustrates a detection and identification system according to the invention, mounted in cascade and

5 - Figure 4 illustrates the operation of the detection and identification method according to the invention when an object is detected; - Figures 5A, 5B and 5C are respectively a top view, a front view and a side view of a rack of receiver modules of equipment containing keys according to the invention, partially represented;

- Figure 3 diagrammatically illustrates the implementation of the detection and identification method according to the invention for a group of modules receiving objects;

antennae currently provided in the applications of this principle are of the order of 5 to 80 cm.

In the detection and identification method according to the invention diagrammatically illustrated in Figure 2, two  
5 antennae A3, Ai are used, electrically looped in a simple manner, which allow, without a power supply or an electronic processing device, change in the induction and data transmission phenomenon, and therefore the entire principle of proximity radio frequency identification of  
10 the prior art.

In this method according to the invention, the power supply of the electronics of a reader produces an induced current in an antenna A3. This current, reduced by line losses, takes place in the antenna coil Ai.

15 If the distance between the antenna A0 and the antenna Ai is sufficiently small as to allow the induction of a sufficient current, the electronics of the identifier sends its radio frequency number via the antenna A0. This number is picked up by the antenna Ai, retransmitted by the cable  
20 to the antenna A3, which retransmits it to the antenna A2. This number is then picked up by the antenna A2 and decoded by the electronics of the reader.

The detection and identification method according to the invention can be used for a group of receiver modules, as  
25 is illustrated diagrammatically by Figure 3. For this purpose, an analogue switch device is used which permits to realize a multiplexing of the antennae each associated with identifiers. In this configuration, multiple identifiers I1, ..., Ii, ..., In can be positioned in front of different  
30 antennae A1, ..., Ai, ..., An.

Different stages of the method according to the invention will now be described with reference to Figure 4 which diagrammatically illustrates a detection and identification system comprising a plurality of receiver  
35 modules.

The detection and identification device 1 comprises, with reference to Figure 1, a group of receiver modules M1, ..., Mi, ..., Mn each provided with a receiver module antenna A1, ..., Ai, ...An, a secondary antenna 3 connected  
40 in parallel to the antennae of the receiver module A1...,



5     A1, ..., An, via a group S of analogue switches S1, ..., S1, ..., Sn, a primary antenna 2 in inductively coupled with the secondary antenna 3, a reading device 10 which includes a reader module 4 and an energy supply module 4, a control and processing unit 6 and a module 7 for sequential control of the analogue switches.

10     When an object 0 provided with an identifier circuit Io and a transmission antenna A0 is situated (stage I) sufficiently close to an antenna of the module A1 so that its antenna A0 is electromagnetically coupled to this antenna of the module A1, the switching (stage II) to the closed position of the switch S1 associated with this module M1 will thus allow, via the inductive coupling between the two antennae primary 2 and secondary 3 respectively and via the inductive coupling between the antenna of the module A1 and the transmission antenna A0 inside the object, an energy transfer (stage III) in order to supply power to the identifier circuit I of this object.

20     The latter transmits back, via the same channel, identification data which are received by the antenna A1, transmitted by induced current and retransmitted by the primary antenna 3, picked up by the primary antenna A2 (stage IV) and decoded (and read) (stage V) by the reader module 4, then processed by the control and processing unit. 25     The detection and identification method according to the invention can have applications for the recognition and control of access to multiple objects equipped with radio frequency (RF) identifiers and placed in a specific place, for example a lockable cabinet, a filling cabinet or a weapons locker. 30     It is important to note that in all the applications mentioned above, the detection and identification method according to the invention also allows information or data to be transferred to the objects identified and this information or data to be entered into memory components provided in the identification electronics of these objects.

35     In one embodiment example of a controlled access system with keys or bunches of keys, receiver modules M1-M5 of keys C1-C5, belonging to a group 100 of modules arranged in a linear fashion, equipped with locking devices are placed 40

on a support plate 101, for example a printed circuit board, as illustrated by Figures 5A to 5D.

Each receiver module M1 comprises a housing 71 designed to receive the active part of a key C1 which includes a  
5 small glass tube 50 containing, according to techniques known in the field of RFID identification, identification electronics and a miniaturized cylindrical winding. The active part of the key C1 also comprises two recesses 51.1, 51.2 arranged so as to receive the mobile shaft 61 of a  
10 locking electromagnet E1 the fixed part 60 of which is attached to the support plate 101. This electromagnet E1 is also provided with a spring 62 which by default holds the mobile shaft 61 in the locking position of a key inserted into the receiver module M1.

15

When a key C1 is effectively inserted into a receiver module M1, its identification electronics 50 are electromagnetically coupled to a receiver antenna 73 arranged on a support plate 72 and electrically connected  
20 to an antennae switching device S of the type diagrammatically represented in Figure 4.

The receiver antenna 73 can for example be produced in the form of a printed circuit on a board made of epoxy resin or any other material supporting printed circuits.

25 The receiver module M1 also comprises, at the bottom of the receiver housing 71, a contactor component 70 provided with a mobile contact stud 75 arranged so that when a key C1 is inserted into the receiver housing 71, the end 52 of the key C1 pushes the contact stud 75, which allows, by  
30 means of an electrical circuit (not represented) which includes the contactor 70, detection of the insertion of a key into this receiver module M1. This information on the insertion is for example processed in order to selectively supply the electromagnet corresponding to this receiver  
35 module, thus helping to significantly reduce the electrical energy consumed, compared to another technical solution which consists of supplying power to all of the electromagnets of a complete system.

The receiver modules M1 also comprise, with reference to  
40 Figure 5D, cylindrical frontal housings provided in order

to contain light emitting diodes (LED) 77 whose selective power supply provides the user of the system with an indication of the receiver module or modules and the respective container or containers which this user is authorized to access. 5

It should be noted that the reception antenna of the receiver module can have many other shapes and geometries than those of the antenna represented in Figures 5C and 5D. It can for example be produced in the form of a solenoid with a fine conducting wire wound around a template having any section whatever, for example circular or square. A reception antenna of the solenoid type can also be envisaged wound around a complete cylinder made of soft ferromagnetic material in order to increase the axial detection range. 15

More generally, a large variety of possible geometries exist for pairs of antennae used in RFID technology. It is sufficient to produce an adaptation of the geometries and number of respective coils of the two antennae which are to be electromagnetically coupled. 20

In a particular embodiment of a key ring which can be used in a lockable cabinet or a key shelf according to the invention, illustrated by Figures 6A and 6B, the key ring C comprises at the end of its active part a part 52 with a pseudo elliptical shape allowing the shaft 61 of the electromagnet E1 to be raised during the insertion of the active part of the key ring C into the housing of the receiver module M1. The cavity provided in the active part of the key ring C is designed to receive a small glass tube with a diameter of 2.12 mm and a length of 12 mm containing an electronic component. 25 30

The key ring C comprises two recesses 51.1, 51.2 designed for receiving in the locking position a mobile shaft of a locking electromagnet and two lateral parts 54.1, 54.2 extending parallel from the active part of the key ring and a toothed central part 53 of the key ring also extending from the active part of the key ring and designed to be engaged in a non-reversible manner in a housing 56 arranged in a closing part 56 when keys have previously been placed in the key ring C. 35 40

It is possible to produce an identification and detection system according to the invention by cascading several electromagnetic coupling/electrical link sections, as illustrated in Figure 7.

Thus, a detection and identification system in cascade SC can comprise, between on the one hand a fixed antenna  $A_i$  of the receiver module designed to be electromagnetically coupled to the antenna  $A_o$  of an object provided with an identifier circuit I and on the other hand a secondary fixed antenna  $A_3$  permanently electromagnetically coupled to an antenna  $A_2$  of a reader module L which includes reading electronics EL carrying out power supply and decoding functions:

- a first electrical link 101 between the antenna  $A_i$  of the receiver module and a first secondary antenna 102 electromagnetically coupled 110 to a first primary intermediate antenna 103,
- a second electrical link 104 between the first primary intermediate antenna 103 and a second secondary intermediate antenna 105 electromagnetically coupled 111 to a second primary intermediate antenna 106, and
- a second electrical link 107 between the second primary intermediate antenna 106 and the secondary fixed antenna  $A_3$ .

The link between the secondary fixed antenna  $A_3$  associated with the reader module and the antenna  $A_i$  of the receiver module is thus ensured by a cascade of two link sections T1, T2 each comprising an electrical link between two antennae of a section and an electromagnetic coupling between a primary intermediate antenna of this section and a secondary intermediate antenna of the following section.

This detection and identification system in cascade SC can of course include a switching system S of the type represented in Figure 3 in order to allow the processing of a group of receiver modules each equipped with a reception antenna.

The detection and identification method can also be used in a system for the detection and identification of

vehicles in parking spaces, as illustrated diagrammatically in Figure 8.

A system for the detection and identification of vehicles SP can thus comprise, in close proximity to each space of a group of parking spaces P1, P2, P3, P4, receiver modules MP1, MP2, MP3, MP4 each provided with a reception antenna A11, A12, A13, A14 electrically connected, via a switching system S, to a common secondary antenna A3 permanently electromagnetically coupled to an antenna A2 of a reader module L carrying out power supply and decoding functions and delivering detection and identification data to a processing device designed in particular to control the switching device S.

When vehicles Vj, Vk, Vl, each provided with identifier devices Ij, Ik, Il which each include an identification antenna, are parked in a parking space P1, P4, P3, their respective identification antennae are electromagnetically coupled to the respective reception antennae A11, A14, A13 of said spaces, which induces a power supply of the identifier devices Ij, Ik, Il and, in return, a transfer of identification information from the identifier devices to the common reader module L.

These identifier devices can be produced for example in the form of RFID tags integrated or inserted into the number plates of the vehicles or in any other appropriate part of the vehicle in order to allow an electromagnetic coupling with a reception antenna associated with a parking space. It can also be envisaged that a vehicle Vk is equipped with two identifiers devices Ik, Ik' integrated in the front and rear number plates of this vehicle.

In another embodiment of a vehicle detection and identification system, it can be envisaged that the reception antennae associated with each parking space are induction loops buried in the surfacing of these parking spaces, each vehicle concerned being provided with an identifier device of the RFID type fixed to its chassis or arranged in a appropriate place in the vehicle.

Of course, the invention is not limited to the examples which have just been described and numerous variations can

- 13 -

be applied to these examples without exceeding the scope of the invention.

CLAIMS

1. Method for the detection and identification of an object provided with identification means and wireless transmission means, this object being present close to one receiver module among a plurality of receiver modules, this method comprising:
- an electromagnetic coupling between the wireless transmission means of said object and a fixed antenna associated with said receiver module, and
  - an electrical coupling between said fixed antenna of the receiver module and a secondary fixed antenna common to all of said fixed antennae of the receiver module, this common secondary fixed antenna being electromagnetically coupled to a primary fixed antenna connected to a reader module which is designed to read identification data originating from said identification means.
- 20 2. Method according to claim 1, characterized in that it also comprises a transmission of information from the reader module to the identification means of a previously detected and identified object.
- 25 3. Method according to claim 2, characterized in that it also comprises writing of information transmitted from the reader module into information storage means within a previously detected and identified object.
- 30 4. Method according to one of the previous claims, characterized in that the secondary fixed antenna is electrically coupled to each of the fixed antenna of each receiver module in succession.
- 35 5. Method according to one of the previous claims, characterized in that each electromagnetic coupling between a fixed antenna of a receiver module and wireless transmission means of an object induces a supply to the identification means within said object, by inductive

coupling, of electrical energy originating from a power supply module connected to the primary fixed antenna.

5 6. Method according to claim 5, characterized in that each electromagnetic coupling between a fixed antenna of a receiver module and wireless transmission means of an object induces a transmission of identification data transmitted by the identification means of said object towards the reader module.

10

7. Method according to one of the previous claims, characterized in that it also comprises a processing of the identification data originating from the identification means of an object, and a selective control of  
15 blocking/locking means which are associated with the receiver module the antenna of which is electromagnetically coupled to the wireless transmission means of said object.

8. Method according to one of the previous claims,  
20 comprising:

- an electromagnetic coupling between the wireless transmission means of said object and a fixed reception antenna associated with a receiver module,
- a permanent electromagnetic coupling between a  
25 secondary fixed reading antenna and an antenna of a reader module,

characterized in that the secondary fixed reading antenna is connected to the fixed reception antenna via a plurality of link sections in cascade each comprising an electrical  
30 link between a secondary intermediate antenna of said link section and a primary intermediate antenna of said link section and an electromagnetic coupling between said primary intermediate antenna and a secondary intermediate antenna of a following link section.

35

9. Device for the detection and identification of an object provided with identification means and wireless transmission means, this object being present close to one receiver module among a plurality of receiver modules, this  
40 device comprising:



- a plurality of fixed antennae each associated with one receiver module among the plurality of receiver modules, means for selectively connecting one antenna of said plurality of fixed antennae to a common secondary fixed antenna, a primary fixed antenna electromagnetically coupled to the secondary fixed antenna, and

- a common reader module designed to read identification data originating from said identification means, this reader module being connected to the primary fixed antenna.

10. Device according to claim 9, characterized in that the common reader module is also designed to transmit information to an object close to a receiver module.

11. Device according to one of claims 9 or 10, characterized in that the selective connection means are arranged in order to connect each fixed antenna of the module to the secondary fixed antenna in sequence.

12. Device according to one of claims 9 to 11, characterized in that it also comprises a power supply module connected to the primary fixed antenna, this module being arranged in order to transmit electrical energy to the identification means of an object the wireless transmission means of which are inductively coupled to a fixed antenna of a receiver module, via the electromagnetic coupling between the primary fixed antenna and the secondary antenna and the electromagnetic coupling between the fixed antenna of the receiver module and the wireless transmission means of said object.

13. Device according to one of claims 10 to 12, characterized in that the common secondary antenna is electromagnetically coupled to a primary intermediate antenna, this primary intermediate antenna being electromagnetically connected to a secondary intermediate antenna coupled to the primary fixed antenna electrically connected to the reader module.

14. Device according to claim 13, characterized in that it also comprises a plurality of pairs of intermediate antennae each constituted by a primary intermediate antenna and a secondary intermediate antenna which are electrically  
5 connected.

15. Equipment for securely storing a plurality of objects each provided with identification means and wireless transmission means, comprising:

- 10 - a group of modules each designed to receive one object among said plurality of objects, each receiver module comprising means for selectively blocking/locking an object, and
  - means for controlling said selective blocking/locking  
15 means,
- characterized in that it also comprises a plurality of fixed antennae each associated with one receiver module among the plurality of receiver modules,
- means for selectively connecting one antenna among said  
20 plurality of fixed antennae to a common secondary fixed antenna, and
  - a primary fixed antenna electromagnetically coupled to the secondary fixed antenna, and
  - a common reader module designed to read identification  
25 data originating from said identification means, this reader module being connected to the primary fixed antenna and cooperating with the control means.

16. Equipment according to claim 15, characterized in that  
30 it also comprises electrical supplying means connected to the primary fixed antenna, which are arranged in order to supply power to the identification means of an object the wireless transmission means of which are inductively coupled to one antenna of one of the receiver modules of  
35 said equipment.

17. Equipment according to one of claims 15 or 16, designed for the management of a set of keys, characterized in that each receiver module comprises:

40 it also comprises means for mechanical coupling with  
 radiofrequency with a receiver module characterized in that  
 means designed to exchange information by proximity  
 comprising identification means and wireless transmission  
 identification method according to one of claims 1 to 8,  
 35 21. Object designed to be processed by a detection and  
 identification means and wireless transmission means.  
 20. Equipment according to one of claims 15 or 16, designed  
 to store in a secure manner weapons provided with  
 30 identification means and wireless transmission means.  
 the first part.  
 receiving the non-reversible mechanical coupling part of  
 - a second part comprising at least one housing for  
 - a non-reversible mechanical coupling part, and  
 25 blocking/locking electromagnet,  
 - an indented part for receiving the mobile part of a  
 and the identification means,  
 - a head which includes the wireless transmission means  
 - a first part comprising:  
 20 comprises:  
 characterized in that the mechanical coupling part  
 19. Equipment according to one of claims 17 or 18,  
 object.  
 15 transmission means and the identification means of the  
 an substantially cylindrical cavity, the wireless  
 the mechanical coupling part has one end which comprises in  
 18. Equipment according to claim 17, characterized in that  
 order to engage in said mechanical coupling part.  
 10 - an electromagnet comprising a mobile part arranged in  
 engaged in the receiver housing, and  
 means of an object the mechanical coupling part of which is  
 between said fixed antenna and the wireless transmission  
 5 housing so as to produce an electromagnetic coupling  
 - a fixed antenna of the module arranged close to said  
 wireless transmission means,  
 part of a key or a ring, this part including the  
 - a housing arranged to receive a mechanical coupling

selective blocking/locking means arranged in said receiver module.

22. Application of the method according to one of claims 1 to 8, for the management of keys or bunches of keys in a lockable cabinet.

23. Application of the method according to one of claims 1 to 8, for the management of documents in a filing cabinet.

24. Application of the method according to one of claims 1 to 8, for the management of weapons in a weapons locker.

25. Application of the method according to one of claims 1 to 8, for the identification of a vehicle in a parking space.

26. System for the detection and identification of a vehicle in a parking space of a parking area, using the method according to one of claims 1 to 8, characterized in that this parking space comprises a fixed reception antenna electrically connected to a primary antenna common to all of the parking spaces of said parking area and electromagnetically coupled to an antenna of a common reader module, said vehicle being equipped with an identifier module comprising an antenna arranged within said vehicle in order to be electromagnetically coupled to the fixed reception antenna of said parking space when said vehicle is parked in said parking space.

27. System according to claim 26, characterized in that the identifier module of the vehicle is included in one and/or more of the number plates of said vehicle.

28. System according to claim 27, characterized in that the identifier module of the vehicle is provided in the form of a radiofrequency tag (RF tag).




FIG. 1




FIG. 2




FIG.3




FIG.5D




Fig. 4

